

**Übersicht der ETL (UL / CSA) zertifizierten Leuchten der LED2WORK GmbH /
List of ETL (UL / CSA) certified luminaires of LED2WORK GmbH**

Bestell-Nummer / article number	Modell / Typ / Bezeichnung model / type / name	Zolltarif-Nummer / customs tariff number
CENALED SPOT, 5000K		
121012-01	CENALED SPOT, Flexarm / flexible arm, 30° - 8,5W, 24V DC	94054239
121012-02	CENALED SPOT, Gelenkarm / articulated arm, 30° - 8,5W, 24V DC	94054139
121012-03	CENALED SPOT, Gelenkkopf / pivoted head, 30° - 8,5W, 24V DC	94054139
UNILED SL, 5200K-5700K		
110914-11	UNILED SL, 295mm, 100° - 15W, 24V DC	94054139
110914-12	UNILED SL, 545mm, 100° - 24W, 24V DC	94054139
110914-13	UNILED SL, 1045mm, 100° - 48W, 24V DC	94054139
110914-14	UNILED SL, 1545mm, 100° - 72W, 24V DC	94054139
FIELDLED II - Einbauversion / integrated luminaires, 5200K-5700K		
113010-11	FIELDLED II, 300x96x30mm, 120° - 20W, 24V DC	94054139
113110-11	FIELDLED II, 560x96x30mm, 120° - 36W, 24V DC	94054139
113210-11	FIELDLED II, 810x96x30mm, 120° - 56W, 24V DC	94054139
113310-11	FIELDLED II, 1060x96x30mm, 120° - 72W, 24V DC	94054139
FIELDLED II - Aufbauversion / surface-mounted luminaires, 5200K-5700K		
113010-01	FIELDLED II, 280x96x30mm, 120° - 20W, 24V DC	94054139
113110-01	FIELDLED II, 540x96x30mm, 120° - 36W, 24V DC	94054139
113210-01	FIELDLED II, 790x96x30mm, 120° - 56W, 24V DC	94054139
113310-01	FIELDLED II, 1040x96x30mm, 120° - 72W, 24V DC	94054139
LEANLED II, 5200K-5700K		
111010-01	LEANLED II 180mm, klare Abdeckung / clear cover, 120° - 4W, 24V DC	94054139
111010-02	LEANLED II 260mm, klare Abdeckung / clear cover, 120° - 6W, 24V DC	94054139
111010-03	LEANLED II 350mm, klare Abdeckung / clear cover, 120° - 8W, 24V DC	94054139
111010-04	LEANLED II 520mm, klare Abdeckung / clear cover, 120° - 13W, 24V DC	94054139
111010-05	LEANLED II 760mm, klare Abdeckung / clear cover, 120° - 19W, 24V DC	94054139
111010-06	LEANLED II 1020mm, klare Abdeckung / clear cover, 120° - 24W, 24V DC	94054139
111010-07	LEANLED II 1520mm, klare Abdeckung / clear cover, 120° - 37W, 24V DC	94054139
111010-11	LEANLED II 180mm, weiße Abdeckung / milky cover, 120° - 4W, 24V DC	94054139
111010-12	LEANLED II 260mm, weiße Abdeckung / milky cover, 120° - 6W, 24V DC	94054139
111010-13	LEANLED II 350mm, weiße Abdeckung / milky cover, 120° - 8W, 24V DC	94054139
111010-14	LEANLED II 520mm, weiße Abdeckung / milky cover, 120° - 13W, 24V DC	94054139
111010-15	LEANLED II 760mm, weiße Abdeckung / milky cover, 120° - 19W, 24V DC	94054139
111010-16	LEANLED II 1020mm, weiße Abdeckung / milky cover, 120° - 24W, 24V DC	94054139
111010-17	LEANLED II 1520mm, weiße Abdeckung / milky cover, 120° - 37W, 24V DC	94054139
LEANLED II - kaskadierbar / cascable, 5200K-5700K		
111010-21	LEANLED II 180mm, klare Abdeckung / clear cover, 120° - 4W, 24V DC, kaskadierbar / cascable	94054139
111010-22	LEANLED II 260mm, klare Abdeckung / clear cover, 120° - 6W, 24V DC, kaskadierbar / cascable	94054139
111010-23	LEANLED II 350mm, klare Abdeckung / clear cover, 120° - 8W, 24V DC, kaskadierbar / cascable	94054139
111010-24	LEANLED II 520mm, klare Abdeckung / clear cover, 120° - 13W, 24V DC, kaskadierbar / cascable	94054139
111010-25	LEANLED II 760mm, klare Abdeckung / clear cover, 120° - 19W, 24V DC, kaskadierbar / cascable	94054139
111010-26	LEANLED II 1020mm, klare Abdeckung / clear cover, 120° - 24W, 24V DC, kaskadierbar / cascable	94054139
111010-27	LEANLED II 1520mm, klare Abdeckung / clear cover, 120° - 37W, 24V DC, kaskadierbar / cascable	94054139
111010-31	LEANLED II 180mm, weiße Abdeckung / milky cover, 120° - 4W, 24V DC, kaskadierbar / cascable	94054139
111010-32	LEANLED II 260mm, weiße Abdeckung / milky cover, 120° - 6W, 24V DC, kaskadierbar / cascable	94054139
111010-33	LEANLED II 350mm, weiße Abdeckung / milky cover, 120° - 8W, 24V DC, kaskadierbar / cascable	94054139
111010-34	LEANLED II 520mm, weiße Abdeckung / milky cover, 120° - 13W, 24V DC, kaskadierbar / cascable	94054139
111010-35	LEANLED II 760mm, weiße Abdeckung / milky cover, 120° - 19W, 24V DC, kaskadierbar / cascable	94054139
111010-36	LEANLED II 1020mm, weiße Abdeckung / milky cover, 120° - 24W, 24V DC, kaskadierbar / cascable	94054139
111010-37	LEANLED II 1520mm, weiße Abdeckung / milky cover, 120° - 37W, 24V DC, kaskadierbar / cascable	94054139
TUBELED_40 II, 5200K-5700K		
118010-01	TUBELED_40 II, 190mm, 5200-5700K, 100° 8W, 24V DC - Power	94054139
118010-11	TUBELED_40 II, 190mm, 5200-5700K, 100° ~8W, 24V DC - Power, kaskadierbar / cascable	94054139
118010-02	TUBELED_40 II, 190mm, 5200-5700K, 100° ~4W, 24V DC - Eco	94054139
118010-12	TUBELED_40 II, 190mm, 5200-5700K, 100° ~4W, 24V DC - Eco, kaskadierbar / cascable	94054139
118110-01	TUBELED_40 II, 280mm, 5200-5700K, 100° ~12W, 24V DC - Power	94054139
118110-11	TUBELED_40 II, 280mm, 5200-5700K, 100° ~12W, 24V DC - Power, kaskadierbar / cascable	94054139
118110-02	TUBELED_40 II, 280mm, 5200-5700K, 100° ~6W, 24V DC - Eco	94054139
118110-12	TUBELED_40 II, 280mm, 5200-5700K, 100° ~6W, 24V DC - Eco, kaskadierbar / cascable	94054139
118210-01	TUBELED_40 II, 365mm, 5200-5700K, 100° ~16W, 24V DC - Power	94054139
118210-11	TUBELED_40 II, 365mm, 5200-5700K, 100° ~16W, 24V DC - Power, kaskadierbar / cascable	94054139
118210-02	TUBELED_40 II, 365mm, 5200-5700K, 100° ~8,5W, 24V DC - Eco	94054139
118210-12	TUBELED_40 II, 365mm, 5200-5700K, 100° ~8,5W, 24V DC - Eco, kaskadierbar / cascable	94054139
118310-01	TUBELED_40 II, 540mm, 5200-5700K, 100° ~24W, 24V DC - Power	94054139
118310-11	TUBELED_40 II, 540mm, 5200-5700K, 100° ~24W, 24V DC - Power, kaskadierbar / cascable	94054139
118310-02	TUBELED_40 II, 540mm, 5200-5700K, 100° ~13W, 24V DC - Eco	94054139
118310-12	TUBELED_40 II, 540mm, 5200-5700K, 100° ~13W, 24V DC - Eco, kaskadierbar / cascable	94054139

**Übersicht der ETL (UL / CSA) zertifizierten Leuchten der LED2WORK GmbH /
List of ETL (UL / CSA) certified luminaires of LED2WORK GmbH**

Bestell-Nummer / article number	Modell / Typ / Bezeichnung model / type / name	Zolltarif-Nummer / customs tariff number
118410-01	TUBELED_40 II, 715mm, 5200-5700K, 100° ~32W, 24V DC - Power	94054139
118410-11	TUBELED_40 II, 715mm, 5200-5700K, 100° ~32W, 24VDC - Power, kaskadierbar / cascable	94054139
118410-02	TUBELED_40 II, 715mm, 5200-5700K, 100° ~17W, 24V DC - Eco	94054139
118410-12	TUBELED_40 II, 715mm, 5200-5700K, 100° ~17W, 24V DC - Eco, kaskadierbar / cascable	94054139
118510-01	TUBELED_40 II, 1040mm, 5200-5700K, 100° ~48W, 24V DC - Power	94054139
118510-11	TUBELED_40 II, 1040mm, 5200-5700K, 100° ~48W, 24V DC - Power, kaskadierbar / cascable	94054139
118510-02	TUBELED_40 II, 1040mm, 5200-5700K, 100° ~24W, 24V DC - Eco	94054139
118510-12	TUBELED_40 II, 1040mm, 5200-5700K, 100° ~24W, 24V DC - Eco, kaskadierbar / cascable	94054139
118610-01	TUBELED_40 II, 1540mm, 5200-5700K, 100° ~72W, 24V DC - Power	94054139
118610-11	TUBELED_40 II, 1540mm, 5200-5700K, 100° ~72W, 24V DC - Power, kaskadierbar / cascable	94054139
118610-02	TUBELED_40 II, 1540mm, 5200-5700K, 100° ~38W, 24V DC - Eco	94054139
118610-12	TUBELED_40 II, 1540mm, 5200-5700K, 100° ~38W, 24V DC - Eco, kaskadierbar / cascable	94054139
TUBELED_40 II integrated		
151010-01	TUBELED_40 II integrated, 220x74x3mm, 100° ~8W, 24V DC - Power	94054139
151110-01	TUBELED_40 II integrated, 395x74x3mm, 100° ~16W, 24V DC - Power	94054139
151210-01	TUBELED_40 II integrated, 570x74x3mm, 100° ~24W, 24V DC - Power	94054139
151310-01	TUBELED_40 II integrated, 745x74x3mm, 100° ~24W, 24V DC - Power	94054139
152010-01	TUBELED_40 II integrated, 340x78x3mm, 100° ~12W, 24V DC - Power	94054139
152210-01	TUBELED_40 II integrated, 700x78x3mm, 100° ~24W, 24V DC - Power	94054139
151010-02	TUBELED_40 II integrated, 220x74x3mm, 100° ~4W, 24V DC - ECO	94054139
151110-02	TUBELED_40 II integrated, 395x74x3mm, 100° ~8,5W, 24V DC - ECO	94054139
151210-02	TUBELED_40 II integrated, 570x74x3mm, 100° ~13W, 24V DC - ECO	94054139
151310-02	TUBELED_40 II integrated, 745x74x3mm, 100° ~13W, 24V DC - ECO	94054139
152010-02	TUBELED_40 II integrated, 340x78x3mm, 100° ~6W, 24V DC - ECO	94054139
152210-02	TUBELED_40 II integrated, 700x78x3mm, 100° ~13W, 24V DC - ECO	94054139
TUBELED_70 - 24V DC, 5200K-5700K		
110310-01	TUBELED_70, 300mm, 100° - 15W, 24V DC	94054139
110314-01	TUBELED_70, 300mm, 60° - 15W, 24V DC	94054139
110410-02	TUBELED_70, 560mm, 100° - 27W, 24V DC	94054139
110414-02	TUBELED_70, 560mm, 60° - 27W, 24V DC	94054139
110510-02	TUBELED_70, 1100mm, 100° - 54W, 24V DC	94054139
110514-02	TUBELED_70, 1100mm, 60° - 54W, 24V DC	94054139
110710-02	TUBELED_70, 1580mm, 100° - 80W, 24V DC	94054139
110714-02	TUBELED_70, 1580mm, 60° - 80W, 24V DC	94054139
INROLED_25, 5200K-5700K		
117010-01	INROLED_25, 348mm, 100° - 4,5W, 24V DC	94054039
117110-01	INROLED_25, 552mm, 100° - 7,5W, 24V DC	94054039
117210-01	INROLED_25, 952mm, 100° - 13W, 24V DC	94054039
INROLED_50_Ecolab, POWER, 5200K-5700K		
110010-01	INROLED_50_Ecolab, 305mm, 100° ~12W, 24V DC - Power	94054039
110110-01	INROLED_50_Ecolab, 565mm, 100° ~24W, 24V DC - Power	94054039
110210-01	INROLED_50_Ecolab, 1065mm, 100° ~48W, 24V DC - Power	94054039
INROLED_50_Ecolab, ECO, 5200K-5700K		
110010-02	INROLED_50_Ecolab, 305mm, 100° - 6,5W, 24V DC - ECO	94054039
110110-02	INROLED_50_Ecolab, 565mm, 100° - 13W, 24V DC - ECO	94054039
110210-02	INROLED_50_Ecolab, 1065mm, 100° - 26W, 24V DC - ECO	94054039
INROLED_70, 5200-5700K		
115010-01	INROLED_70, 354mm, 125° - 8W, 24V DC, kaskadierbar / cascable	94054139
115110-01	INROLED_70, 513mm, 125° - 12W, 24V DC, kaskadierbar / cascable	94054139
115210-01	INROLED_70, 650mm, 125° - 13W, 24V DC, kaskadierbar / cascable	94054139
115310-01	INROLED_70, 921mm, 125° - 20W, 24V DC, kaskadierbar / cascable	94054139
115410-01	INROLED_70, 1214mm, 125° - 24W, 24V DC, kaskadierbar / cascable	94054139
UNILED SL, RGB-W		
110994-11	UNILED SL, RGB-W, 295mm, 100° - ~20,5W + 9,5W, 24V DC	94054239
110994-12	UNILED SL, RGB-W, 545mm, 100° - ~41W + 19W, 24V DC	94054239
110994-13	UNILED SL, RGB-W, 1045mm, 100° - ~82W + 38W, 24V DC	94054239
110994-14	UNILED SL, RGB-W, 1545mm, 100° - ~123W + 57W, 24V DC	94054239
TUBELED_40 II_RGB-W - POWER		
118190-01	TUBELED_40 II_RGB-W, 280mm, 100° - ~20,5W + 9,5W, 24V DC	94054239
118390-01	TUBELED_40 II_RGB-W, 540mm, 100° - ~41W + 19W, 24V DC	94054239
118590-01	TUBELED_40 II_RGB-W, 1040mm, 100° - ~82W + 38W, 24V DC	94054239
118690-01	TUBELED_40 II_RGB-W, 1540mm, 100° - ~123W + 57W, 24V DC	94054239

**Übersicht der ETL (UL / CSA) zertifizierten Leuchten der LED2WORK GmbH /
List of ETL (UL / CSA) certified luminaires of LED2WORK GmbH**

Bestell-Nummer / article number	Modell / Typ / Bezeichnung model / type / name	Zolltarif-Nummer / customs tariff number
TUBELED_40 II_RGB-W - ECO		
118190-02	TUBELED_40 II_RGB-W, 280mm, 100° ~8W + 6W, 24V DC	94054239
118390-02	TUBELED_40 II_RGB-W, 540mm, 100° ~16W + 13W, 24V DC	94054239
118590-02	TUBELED_40 II_RGB-W, 1040mm, 100° ~32W + 24W, 24V DC	94054239
118690-02	TUBELED_40 II_RGB-W, 1540mm, 100° ~48W + 38W, 24V DC	94054239
TUBELED_40 II_RGB-W integrated		
151190-01	TUBELED_40 II integrated_RGB-W, 395x74x3mm, 100° ~9W(R)/2,5W(G)/9W(B)+9,5W(W), 24V DC	94054239
151290-01	TUBELED_40 II integrated_RGB-W, 570x74x3mm, 100° ~18W(R)/5W(G)/18W(B)+19W(W), 24V DC	94054239
151390-01	TUBELED_40 II integrated_RGB-W, 745x74x3mm, 100° ~18W(R)/5W(G)/18W(B)+19W(W), 24V DC	94054239
152090-01	TUBELED_40 II integrated_RGB-W, 340x78x3mm, 100° ~9W(R)/2,5W(G)/9W(B)+9,5W(W), 24V DC	94054239
152290-01	TUBELED_40 II integrated_RGB-W, 700x78x3mm, 100° ~18W(R)/5W(G)/18W(B)+19W(W), 24V DC	94054239
SIGNALED II, RGB		
111090-11	SIGNALED II 180mm, RGB, 120° ~1,8W(R)/1,8W(G)/1,8W(B), 24V DC	94054239
111090-12	SIGNALED II 260mm, RGB, 120° ~2,6W(R)/2,6W(G)/2,6W(B), 24V DC	94054239
111090-13	SIGNALED II 350mm, RGB, 120° ~4,4W(R)/4,4W(G)/4,4W(B), 24V DC	94054239
111090-14	SIGNALED II 520mm, RGB, 120° ~5,3W(R)/5,3W(G)/5,3W(B), 24V DC	94054239
111090-15	SIGNALED II 760mm, RGB, 120° ~7,9W(R)/7,9W(G)/7,9W(B), 24V DC	94054239
111090-16	SIGNALED II 1020mm, RGB, 120° ~10,6W(R)/10,6W(G)/10,6W(B), 24V DC	94054239
111090-17	SIGNALED II 1520mm, RGB, 120° ~15,8W(R)/15,8W(G)/15,8W(B), 24V DC	94054239
INROLED_50_RGB-W_Ecolab		
110090-01	INROLED_50_RGB-W_Ecolab, 305mm, 100° ~9W(R)/2,5W(G)/9W(B)+9,5W(W), 24V DC - Power	94054239
110190-01	INROLED_50_RGB-W_Ecolab, 565mm, 100° ~18W(R)/5W(G)/18W(B)+19W(W), 24V DC - Power	94054239
110290-01	INROLED_50_RGB-W_Ecolab, 1065mm, 100° ~36W(R)/10W(G)/36W(B)+38W(W), 24V DC - Power	94054239