


## LED Arbeitsplatzleuchte LED workplace light



### CENALED SPOT DC, Flexarm

**Artikelnr.:** 121012-01  
**EAN:** 4260556623719

<b>Bestell-Nr.:</b>	121012-01
<b>Modell:</b>	CENALED SPOT
<b>Bauform:</b>	LED Arbeitsplatzleuchte mit Schwanenhals
<b>Leuchtmittel:</b>	High Power LED
<b>Lampenleistung:</b>	~8,5 W
<b>Lampenlichtstrom:</b>	1120 lm
<b>Lampenlichtausbeute:</b>	134 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Neutralweiß (5000K)
<b>Anschlusswert Leuchte:</b>	24V DC ± 10%
<b>Betriebsgerät:</b>	-
<b>Anschluss Leuchte:</b>	3 m Anschlussleitung, Ölflex, mit offenen Leitungsenden
<b>Schutzart:</b>	IP67
<b>Schutzklasse:</b>	III
<b>Abstrahlwinkel:</b>	30°
<b>Betriebstemperatur:</b>	-10... +50 °C
<b>Farbwiedergabe (Ra):</b>	> 80
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Gehäuse:</b>	Aluminium (pulverlackiert)
<b>Material Abdeckung:</b>	Sicherheitsglas, sprungsicher
<b>Länge Flexarm [A]:</b>	500 mm
<b>Sockelhöhe (B):</b>	59 mm
<b>Befestigung:</b>	Anschraubsockel
<b>Gewicht:</b>	800 g
<b>Bruttogewicht:</b>	1400 g
<b>Risikogruppe (DIN EN 62471):</b>	freie Gruppe
<b>Befestigungszubehör:</b>	Magnethalterung optional
<b>Dimmbar:</b>	ja, über Taster am Leuchtenkopf, Ein/Aus und Dimmen
<b>Kennzeichnung:</b>	CE, UKCA, ETL Listed (5003529) (5003529)
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	Universell einsetzbare Arbeitsleuchte mit hoher Schutzart



Lampenlebensdauer in Betriebsstunden (L80/B10)


LED Arbeitsplatzleuchte  
LED workplace light



## CENALED SPOT DC, Flexarm

**Item number:** 121012-01  
**EAN:** 4260556623719

<b>Order number:</b>	121012-01
<b>Model:</b>	CENALED SPOT
<b>Type:</b>	LED workplace light with gooseneck
<b>Illuminant:</b>	High Power LED
<b>Power consumption:</b>	~8,5 W
<b>Lamp luminous flux:</b>	1120 lm
<b>Lamp luminous efficiency:</b>	134 lm/W
<b>Light distribution:</b>	direct
<b>Light colour:</b>	neutral white (5000K)
<b>Connected load:</b>	24V DC ± 10%
<b>Power supply:</b>	-
<b>Connection (connector):</b>	connection cable 3m (9,84ft), flexible, two open cable ends
<b>Degree of protection:</b>	IP67
<b>Class of protection:</b>	III
<b>Beam angle (optics):</b>	30°
<b>Operating temperature:</b>	-10... +50 °C (14... 122 °F)
<b>Colour rendering (Ra):</b>	> 80
<b>Lamps lifetime:</b>	> 60,000 h
<b>Housing material:</b>	aluminium (powder finished)
<b>Cover material:</b>	safety glass, shatterproof
<b>Length Flexarm [A]:</b>	500 mm (19,69")
<b>Base height (B):</b>	59 mm (2,32")
<b>Mounting:</b>	screw-on base
<b>Weight (net):</b>	800 g (~28 oz)
<b>Gross weight:</b>	1400 g (~49 oz)
<b>Risk group (DIN EN 62471):</b>	free group
<b>Mounting accessories:</b>	magnet holder plate optional
<b>Dimmable:</b>	yes, via push button at the luminaire head, ON/OFF and dimming
<b>Marking:</b>	CE, UKCA, ETL Listed (5003529)
<b>Made in:</b>	Germany
<b>Feature:</b>	universal workplace light with high protection degree



Lamps lifetime in operation hours (L80/B10)