LED2WORK
INTELLIGENCE IN LIGHT

LED Arbeitsplatzleuchte
LED workplace light

PROFILED AC, 500 mm, mit Dimmer, Abdeckung Mikroprismen, 90-305V AC

Artikel-Nr.:	150314-04
EAN:	4260556623894







Bestell-Nr.:	150314-04
Modell:	PROFILED
Bauform:	Profilleuchte mit T-Nut rückseitig
Leuchtmittel:	SMD LED
Lampenleistung:	~14 W
Lampenlichtstrom:	1575 lm
Lampenlichtausbeute:	145 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	90-305V AC ± 10%, 50-60 Hz
Betriebsgerät:	integriert
Anschluss Leuchte:	Anschlussleitung mit Netzstecker
Schutzart:	IP40
Schutzklasse:	I
Entblendung:	Mikroprismen
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +45 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Kunststoff
Höhe [B] x Breite [C]:	65 mm x 45 mm
Länge [A]:	500 mm
Gewicht:	1400 g
Bruttogewicht:	1850 g
Risikogruppe (DIN EN 62471):	freie Gruppe
Befestigungszubehör:	optional
Dimmbar:	Dimmer intern
Kennzeichnung:	CE, UKCA
Gefertigt in:	Deutschland
Besonderheit:	Universalleuchte mit Dimmer

Lampenlebensdauer in Betriebstunden (L80/B10)

Datenblätter immer aktuell: www.led2work.com/de/produkte
Datasheets always up to date: www.led2work.com/en/products

LED2WORK GmbH | Stuttgarter Str. 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com | shop.led2work.com

LED Arbeitsplatzleuchte
LED workplace light

PROFILED AC, 500 mm (35,43“), with dimmer micro prisms cover, 90-305V AC

Item number:	150314-04
EAN:	4260556623894







Order number:	150314-04
Model:	PROFILED
Type:	pofiled light with t-slot backsided
Illuminant:	SMD LED
Power consumption:	~14 W
Lamp luminous flux:	1575 lm
Lamp luminous efficiency:	145 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	90-305V AC ± 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	connection cable power plug
Degree of protection:	IP40
Class of protection:	I
Glare-free	micro prisms
Beam angle (optics):	100°
Operating temperature:	-10... +45 °C (14... 113 °F)
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60,000 h
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	65 mm x 45 mm (2,56“ x 1,77“)
Length [A]:	500 mm (35,43“)
Weight (net):	1400 g (~49 oz)
Gross weight:	1850 g (~65 oz)
Risk group (DIN EN 62471):	free group
Mounting accessories:	optional
Dimmable:	internal dimmer control
Marking:	CE, UKCA
Made in:	Germany
Feature:	universal light , dimmable

Lamps lifetime in operation hours (L80/B10)

Datenblätter immer aktuell: www.led2work.com/de/produkte
Datasheets always up to date: www.led2work.com/en/products

LED2WORK GmbH | Stuttgarter Str. 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com | shop.led2work.com