

LED Industrieleuchte



LED industrial luminaire



INROLED_25, 552 mm, 100°, 24V DC

Artikel-Nr.: 117110-01
EAN: 4260556621562

Bestell-Nr.: 117110-01
Modell: INROLED_25
Bauform: LED Rohrleuchte
Leuchtmittel: SMD LED
Lampenleistung: ~7,5 W
Lampenlichtstrom: 972 lm
Lampenlichtausbeute: 129 lm/W
Lichtverteilung: direkt
Lichtfarbe: Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte: 24V DC \pm 10%
Anschluss Leuchte: M12 Steckverbinder A-kodiert
Schutzart: IP69K
Schutzklasse: III
Entblendung: opalweiß
Abstrahlwinkel: 100°
Betriebstemperatur: -10... +50 °C
Farbwiedergabe (Ra): > 80
Lampenlebensdauer: > 60.000 h
Material Abdeckung: Polycarbonat, splitterfrei
Höhe [B] x Breite [C]: \varnothing 25 mm
Länge [A]: 552 mm
Gewicht: 250 g
Bruttogewicht: 400 g
Risikogruppe (DIN EN 62471): freie Gruppe
Befestigungszubehör: Halterung inkl.
Dimmbar: optional über Zubehör
Kennzeichnung: CE, UKCA, ETL Listed
Gefertigt in: Deutschland
Besonderheit: Lebensmittellecht, beständig gegen Säure und Laugen (vorab Einzelfallprüfung)




Lampenlebensdauer in Betriebsstunden (L80/B10)



INROLED_25, 552 mm, 100°, 24V DC

Item number: 117110-01
EAN: 4260556621562

Order number:	117110-01
Model:	INROLED_25
Type:	LED tube luminaire
Illuminant:	SMD LED
Power consumption:	~7,5 W
Lamp luminous flux:	972 lm
Lamp luminous efficiency:	129 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Connection (connector):	M12 connector A-type encoded
Degree of protection:	IP69K
Class of protection:	III
Glare-free	opal white
Beam angle (optics):	100°
Operating temperature:	-10... +50 °C
Colour rendering (Ra):	> 80
Lamps lifetime:	> 60,000 h
Cover material:	polycarbonate, shatterproof
Height [B] x Width [C]:	\varnothing 25 mm
Length [A]:	552 mm
Weight (net):	250 g
Gross weight:	400 g
Risk group (DIN EN 62471):	free group
Mounting accessories:	incl. luminaire holders
Dimmable:	via optional accessory
Marking:	CE, UKCA, ETL Listed
Made in:	Germany
Feature:	food-safe, resistant to acids and alkalis (case-by-case testing before)



Lamps lifetime in operation hours (L80/B10)