




## Maschineneinbauleuchte SPOTLED II, Optik 25° für flächiges Licht

**Artikel-Nr.:** 11112-12  
**EAN:** 4260556620923

<b>Bestell-Nr.:</b>	11112-12
<b>Modell:</b>	SPOTLED II
<b>Bauform:</b>	LED Einbauleuchte
<b>Leuchtmittel:</b>	High Power LED
<b>Lampenleistung:</b>	~8,5 W
<b>Lampenlichtstrom:</b>	982 lm
<b>Lampenlichtausbeute:</b>	116 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	24V DC ± 10%
<b>Anschluss Leuchte:</b>	M12 A-kodiert
<b>Schutzart:</b>	IP67
<b>Schutzklasse:</b>	III
<b>Abstrahlwinkel:</b>	25°
<b>Betriebstemperatur:</b>	-10... +40 °C
<b>Farbwiedergabe (Ra):</b>	> 80
<b>Lampenlebensdauer:</b>	> 50.000 h
<b>Material Gehäuse:</b>	Aluminium
<b>Material Abdeckung:</b>	4 mm Sicherheitsglas
<b>Höhe [B] x Breite [C]:</b>	Ø72 mm, 50 mm einbauend, Blende Ø99 mm, 5 mm aufbauend
<b>Gewicht:</b>	450 g
<b>Bruttogewicht:</b>	550 g
<b>Risikogruppe (DIN EN 62471):</b>	Gruppe 1
<b>Kennzeichnung:</b>	CE
<b>Dimmbar:</b>	optional über Zubehör
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	25° Optik für flächiges Licht
<b>Anmerkung:</b>	Befestigung: Schrauben M5 DIN 74-Am, FKM Dichtung im Lieferumfang




Lampenlebensdauer in Betriebsstunden (L80/B10)



## Recessed luminaire SPOTLED II, optics 25°

**Item number:** 111112-12  
**EAN:** 4260556620923

<b>Order number:</b>	111112-12
<b>Model:</b>	SPOTLED II
<b>Type:</b>	LED recessed luminaire
<b>Illuminant:</b>	High Power LED
<b>Power consumption:</b>	~8,5 W
<b>Lamp luminous flux:</b>	982 lm
<b>Lamp luminous efficiency:</b>	116 lm/W
<b>Light distribution:</b>	direct
<b>Light colour:</b>	daylight white (5200 - 5700K)
<b>Connected load:</b>	24V DC ± 10%
<b>Connection (connector):</b>	M12 A-type encoded
<b>Degree of protection:</b>	IP67
<b>Class of protection:</b>	III
<b>Beam angle (optics):</b>	25°
<b>Operating temperature:</b>	-10... +40 °C
<b>Colour rendering (Ra):</b>	> 80
<b>Lamps lifetime:</b>	> 50,000 h
<b>Housing material:</b>	aluminium
<b>Cover material:</b>	4 mm safety glass
<b>Height [B] x Width [C]:</b>	Ø72 mm, 50 mm inwards, cover plate Ø99 mm, 5 mm externally
<b>Weight (net):</b>	450 g
<b>Gross weight:</b>	550 g
<b>Risk group (DIN EN 62471):</b>	group 1
<b>Marking:</b>	CE
<b>Dimmable:</b>	via optional accessory
<b>Made in:</b>	Germany
<b>Feature:</b>	25° optics for flat light
<b>Explanatory note:</b>	mounting: screws M5 DIN 74-Am, seal FKM in delivery scope



Lamps lifetime in operation hours (L80/B10)