


LED Maschinenleuchte
LED machine luminaire

TUBELED_70, 100°, 1100 mm, 24V DC

Artikel-Nr.: 110510-02
EAN: 4260556621357

Bestell-Nr.: 110510-02
Modell: TUBELED_70 DC
Bauform: LED Aufbauleuchte für Maschinen
Leuchtmittel: High Power LED
Lampenleistung: ~54 W
Lampenlichtstrom: 6064 lm
Lampenlichtausbeute: ca. 132 lm/W
Lichtverteilung: direkt
Lichtfarbe: Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte: 24V DC \pm 10%
Anschluss Leuchte: M12 A-kodiert
Schutzart: IP67/IP69K
Schutzklasse: III
Entblendung: opalweiß
Abstrahlwinkel: 100°
Betriebstemperatur: -30... +70 °C
Farbwiedergabe (Ra): > 85
Lampenlebensdauer: > 60.000 h
Material Gehäuse: Aluminium
Material Abdeckung: Sicherheitsglas gefrostet, sprungsicher
Höhe [B] x Breite [C]: Ø 70 mm
Länge [A]: 1100 mm
Gewicht: 2950 g
Bruttogewicht: 3750 g
Risikogruppe (DIN EN 62471): freie Gruppe
Kennzeichnung: CE, UKCA, ETL Listed (5003526)
Befestigungszubehör: optional
Dimmbar: optional über Zubehör
Gefertigt in: Deutschland
Besonderheit: Retrofitting: genormte LED Rohrleuchte zum 1:1 Austausch



Lampenlebensdauer in Betriebsstunden (L80/B10)


LED Maschinenleuchte
LED machine luminaire



TUBELED_70, 100°, 1100 mm, 24V DC

Item number: 110510-02
EAN: 4260556621357

Order number:	110510-02
Model:	TUBELED_70 DC
Type:	LED surface-mounted luminaire for machines
Illuminant:	High Power LED
Power consumption:	~54 W
Lamp luminous flux:	6064 lm
Lamp luminous efficiency:	ca. 132 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare-free	opal white
Beam angle (optics):	100°
Operating temperature:	-30... +70 °C
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60,000 h
Housing material:	aluminium
Cover material:	Safety glass, frosted, shatterproof
Height [B] x Width [C]:	\varnothing 70 mm
Length [A]:	1100 mm
Weight (net):	2950 g
Gross weight:	3750 g
Risk group (DIN EN 62471):	free group
Marking:	CE, UKCA, ETL Listed (5003526)
Mounting accessories:	optional
Dimmable:	via optional accessory
Made in:	Germany
Feature:	retrofitting: standardised LED luminaire for 1:1 replacement



Lamps lifetime in operation hours (L80/B10)