

LED Zubehör
 LED accessories

 Sensor Kabel, PUR, 10 m, M12 Stecker/M12 Buchse,
 A-kodiert

| | |
|---------------------|---------------|
| Artikel-Nr.: | 200100-03 |
| EAN: | 4260556621883 |

| | |
|--------------------------------|---|
| Bestell-Nr.: | 200100-03 |
| Modell: | LED2WORK Sensor Kabel 0,34 mm ² , für 24V DC |
| Bauform: | Sensor Kabel, PUR, schwarz |
| Kodierung: | A kodiert |
| Geeignet für: | LED2WORK Leuchten 24V DC, außer RGB und RGB-W Leuchten |
| Anzahl: | 1 |
| Länge Kabel: | 10 m |
| Kabelenden: | M12 Stecker, gerade / M12 Buchse, gerade |
| Polzahl: | 4 |
| Bemessungsspannung: | 250V |
| Strombelastung pro PIN: | 4000 mA |
| Umgebungstemperatur: | -30...+90°C |
| Durchgangswiderstand: | < 0,005 Ω |
| Isolationswiderstand: | ≥10 ⁸ Ω |
| Material Kabel: | PUR |
| Material Griffkörper: | Kunststoff, TPU, BK |
| Material_Kontaktträger: | Kunststoff, TPU, BK |
| Material Überwurf: | Metall, CuZn, vernickelt |
| Material Dichtung: | FPM / FKM |
| Material Kontakte: | Metall, CuSn, vergoldet |
| Normen: | IEC 61076-2-101 |
| Befestigung an Leuchte: | Steckverbinder M12 Buchse, gerade |
| RoHS: | 1 |
| UL: | 1 |
| Schutzart (montiert): | IP65, IP67, IP68 |
| Gewicht: | 300 g |
| Bruttogewicht: | 350 g |



Sensor cable, 2,5 m, M12 plug/M12 socket, A-type encoded

| | |
|---------------------|---------------|
| Item number: | 200100-03 |
| EAN: | 4260556621883 |

| | |
|---------------------------------------|---|
| Order number: | 200100-03 |
| Model: | LED2WORK sensor cable 0,34 mm ² , for 24V DC |
| Type: | sensor cable, PUR, black |
| Encoding: | A-type encoded |
| Suitable for: | LED2WORK 24V DC luminaires, except RGB and RGB-W luminaires |
| Quantity: | 1 |
| Length of cable: | 10 m |
| Cable ends: | M12 plug, straight / M12 socket, straight |
| Number of contacts: | 4 |
| Rated voltage: | 250V |
| Current load per PIN: | 4000 mA |
| Operating temperature: | -30... +90°C |
| Resistance: | < 0,005 Ω |
| Insulation resistance: | ≥=10 ⁸ Ω |
| Material cable: | PUR |
| Materials grip body: | plastics, TPU, BK |
| Material contact carrier: | plastics, TPU, BK |
| Material cap: | metal, CuZn, nickel-plated |
| Material seals: | FPM / FKM |
| Materials contacts: | metal, CuSn, gold-plated |
| Standards: | IEC 61076-2-101 |
| Gross weight: | connector M12 socket, straight |
| RoHS: | 1 |
| UL: | 1 |
| Degree of protection (fitted): | IP65, IP67, IP68 |
| Weight (net): | 300 g |
| Gross weight: | 350 g |