

LED Maschinenleuchte



LED machine luminaire



MIDILED LED Aufbauleuchte

Artikel-Nr.:	110614-01
EAN:	4260556620886
Zolltarifnr.:	94054099

Bestellnr.:	110614-01
Modell:	MIDILED
Bauform:	LED Aufbauleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~7 W
Lampenlichtstrom:	609 lm
Lampenlichtausbeute:	ca. 87 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24 V DC
Betriebsgerät:	-
Anschluss Leuchte:	M12 A-kodiert
Schutzart:	IP68
Schutzklasse:	III
Entblendung:	ESG matt, sprungsicher
Abstrahlwinkel:	120°
Betriebstemperatur:	-10... +40 °C
Farbwiedergabe (Ra):	> 80
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Sicherheitsglas gefrostet
Länge [A]:	ca. 148 mm
Gewicht:	400 g
Bruttogewicht:	550 g
Risikogruppe:	freie Gruppe
Befestigungszubehör:	Haltewinkel inklusive
Dimmbar:	optional über Zubehör
Gefertigt in:	Deutschland
Besonderheit:	kompakt, sehr lichtstark



Lampenlebensdauer in Betriebstunden (L80/B10)



LED Maschinenleuchte
LED machine luminaire



MIDILED LED surface mounted luminaire

Item number:	110614-01
EAN:	4260556620886
Customs tariff number:	94054099

Order number:	110614-01
Model:	MIDILED
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Power consumption:	~7 W
Lamp luminous flux:	609 lm
Lamp luminous efficiency:	ca. 87 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24 V DC
Power supply:	-
Connection (connector):	M12 A-type encoded
Degree of protection:	IP68
Class of protection:	III
Glare-free	ESG frosted, shatterproof
Beam angle (optics):	120°
Operating temperature:	-10... +40 °C
Colour rendering (Ra):	> 80
Lamps lifetime:	> 60,000 h
Housing material:	aluminium
Cover material:	safety glass frosted
Length [A]:	ca. 148 mm
Weight (net):	400 g
Gross weight:	550 g
Risk group (DIN EN 62471):	free group
Mounting accessories:	holding angle in delivery scope
Dimmable:	via optional accessory
Made in:	Germany
Feature:	compactly built, very bright



Lamps lifetime in operation hours (L80/B10)