


LED Zubehör  
 LED accessories

**F+B Sensor Kabel, 5 m, offene Enden/M12 Buchse, A-kodiert, für 24V**

<b>Artikel-Nr.:</b>	201100-04
<b>EAN:</b>	4260556622583
<b>Zolltarifnr.:</b>	85444290

<b>Bestellnr.:</b>	201100-04
<b>Modell:</b>	LED2WORK Sensor Kabel, TPE grau, für 24V DC
<b>Bauform:</b>	Sensor Kabel, TPE, grau
<b>Kodierung:</b>	A-kodiert
<b>Geeignet für:</b>	LED2WORK Leuchten 24V DC, außer RGB und RGB-W Leuchten
<b>Anzahl:</b>	1
<b>Länge Kabel:</b>	5 m
<b>Kabelenden:</b>	offene Enden, 4 Adern/ M12 Buchse, gerade
<b>Polzahl:</b>	4
<b>Bemessungsspannung:</b>	250V
<b>Strombelastung pro PIN:</b>	4000 mA
<b>Umgebungstemperatur:</b>	-40...+105°C
<b>Durchgangswiderstand:</b>	< 0,005 Ω
<b>Isolationswiderstand:</b>	≥=10 <sup>8</sup> Ω
<b>Material Kabel:</b>	TPE
<b>Material Griffkörper:</b>	Kunststoff, PP, GY
<b>Material Kontaktträger:</b>	Kunststoff, PP, GY
<b>Material Überwurf:</b>	Edelstahl, V4A
<b>Material Dichtung:</b>	EPDM
<b>Material Kontakte:</b>	Metall, CuSn, vergoldet
<b>Normen:</b>	IEC 61076-2-101
<b>Befestigung an Leuchte:</b>	Steckverbinder M12 Buchse, gerade, Dichtung EPDM, Überwurf V4A
<b>RoHS:</b>	1
<b>UL:</b>	1
<b>Schutzart (montiert):</b>	IP65, IP67, IP68
<b>Gewicht:</b>	200 g
<b>Bruttogewicht:</b>	250 g
<b>Besonderheit:</b>	Food+Beverage geeignet, FDA zugelassen





## Sensor cable for F+B, 5 m, open/M12 socket, A-type encoded

<b>Item number:</b>	201100-04
<b>EAN:</b>	4260556622583
<b>Customs tariff number:</b>	85444290

<b>Order number:</b>	201100-04
<b>Model:</b>	LED2WORK sensor cable, TPE gray, for 24V DC
<b>Type:</b>	sensor cable, TPE, gray
<b>Encoding:</b>	A-type encoded
<b>Suitable for:</b>	LED2WORK 24V DC luminaires, except RGB and RGB-W luminaires
<b>Quantity:</b>	1
<b>Length of cable:</b>	5 m
<b>Cable ends:</b>	open ends, 4 cores / M12 socket, straight
<b>Number of contacts:</b>	4
<b>Rated voltage:</b>	250V
<b>Current load per PIN:</b>	4000 mA
<b>Operating temperature:</b>	-40...+105°C
<b>Resistance:</b>	< 0,005 Ω
<b>Insulation resistance:</b>	≥=10 <sup>8</sup> Ω
<b>Material cable:</b>	TPE
<b>Materials grip body:</b>	plastics, PP, GY
<b>Material contact carrier:</b>	plastics, PP, GY
<b>Material cap:</b>	stainless steel V4A
<b>Material seals:</b>	EPDM
<b>Materials contacts:</b>	metal, CuSn, gold-plated
<b>Standards:</b>	IEC 61076-2-101
<b>Connection:</b>	connector M12 socket, straight, seal EPDM, cap stainless steel
<b>RoHS:</b>	1
<b>UL:</b>	1
<b>Degree of protection (fitted):</b>	IP65, IP67, IP68
<b>Weight (net):</b>	200 g
<b>Gross weight:</b>	250 g
<b>Feature:</b>	especially suitable for Food+Beverage, FDA approved

