


LED tube luminaire



Product-Nr.	110010-03
EAN:	4260556624655
Model:	INROLED_50 Ecolab AC
Order number:	110010-03
Model:	INROLED_50 Ecolab AC
Type:	LED tube luminaire
Illuminant:	SMD LED
Total output incl. driver:	~8,5 W
Power consumption:	~8,5 W
Lamp luminous flux:	1030 lm
Lamp luminous efficiency:	127 lm/W
Light distribution:	direct
Light colour:	5600K 3-step MacAdam
Connected load:	220-240V AC \pm 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	M12 S-coded
Degree of protection:	IP67/IP69K
Class of protection:	I
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-30 °C -> +30 °C (-22 °F -> 86 °F)
Colour rendering (Ra):	>80
Lamps lifetime:	> 100,000 h (L80/B10)
Cover material:	polycarbonate, milky, shatterproof with Ecolab coating
impact resistance:	IK09
Height [B] x Width [C]:	Ø 50 mm (~1,97")
Length [A]:	305 mm (~12,01")
Weight (net):	450 g (~16 oz)
Gross weight:	650 g (~23 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Mounting accessories:	incl. luminaire holder made of metal detectable PP
Made in:	Germany
Feature:	Food+Beverage suitable: Ecolab certified, HACCP certificate