LED2WORK
INTELLIGENCE IN LIGHT

LED-Industrieleuchte

Product-Nr.	110110-03
EAN:	4260556624662
Model:	INROLED_50 Ecolab AC



Order number:	110110-03
Model:	INROLED_50 Ecolab AC
Type:	LED tube luminaire
Illuminant:	SMD LED
Total output incl. driver:	~16 W
Power consumption:	~16 W
Lamp luminous flux:	2004 lm
Lamp luminous efficiency:	~125 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	220-240V AC ± 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	M12 connector S-type encoded
Degree of protection:	IP67/IP69K
Class of protection:	I
Beam angle (optics):	100°
Operating temperature:	-30... +30 °C (-22… 86 °F)
Colour rendering (Ra):	> 80
Lamps lifetime:	> 50.000 h (L80/B10)
Cover material:	polycarbonate, milky, shatterproof with Ecolab coating
impact resistance:	IK09
Height [B] x Width [C]:	Ø 50 mm (Ø 1,97“)
Length [A]:	565 mm (22,24“)
Weight (net):	950 g (~34 oz)
Gross weight:	1150 g (~41 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Mounting accessories:	incl. luminaire holder made of metal detectable PP
Made in:	Germany
Feature:	Food+Beverage suitable: Ecolab certified, HACCP certificate

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com