



## LED-Industrieleuchte mit Signalfunktion



|                                     |   |
|-------------------------------------|---|
| <b>Product-Nr.</b>                  | 110190-01   |
| <b>EAN:</b>                         | 4260556624600   |
| <b>Model:</b>                       | INROLED_50 Ecolab RGB-W                                       |
| Order number:                       | 110190-01   |
| <b>Model:</b>                       | INROLED_50 Ecolab RGB-W                                       |
| <b>Type:</b>                        | LED tube light  |
| <b>Illuminant:</b>                  | SMD RGB-W Cluster LED   |
| <b>Power consumption white:</b>     | ~19 W   |
| <b>White lamp luminous flux:</b>    | ~19 W   |
| <b>Lamp luminous efficiency:</b>    | 126 lm/W  |
| <b>Light colour white:</b>          | daylight white (5200 - 5700K)                                 |
| <b>Power consumption RED:</b>       | ~18 W   |
| <b>Lamp luminous flux RED:</b>      | 480 lm  |
| <b>Power consumption GREEN:</b>     | ~5 W  |
| <b>Lamp luminous flux GREEN:</b>    | 710 lm  |
| <b>Power consumption BLUE:</b>      | ~18 W   |
| <b>Lamp luminous flux BLUE:</b>     | 300 lm  |
| <b>Light distribution:</b>          | direct  |
| <b>Connected load:</b>              | 24 V DC -10 % +7 % (RGB) – 24 V DC $\pm$ 10 % (W)             |
| <b>Connection (connector):</b>      | M12 A-type encoded  |
| <b>Degree of protection:</b>        | IP67/IP69K  |
| <b>Class of protection:</b>         | III   |
| <b>Glare control:</b>               | opal white  |
| <b>Beam angle (optics):</b>         | 100°  |
| <b>Operating temperature:</b>       | -30... +55 °C (several colours +35 °C) (-22... 131 °F; 95 °F) |
| <b>Colour rendering WHITE (Ra):</b> | >85   |
| <b>Lamps lifetime:</b>              | > 60.000 h (L80/B10)  |
| <b>Housing material:</b>            | polycarbonate, soft, shatterproof with Ecolab coating         |
| <b>impact resistance:</b>           | IK09  |
| <b>Height [B] x Width [C]:</b>      | Ø50 mm (Ø 1,97")  |
| <b>Length [A]:</b>                  | 565 mm (22,24")   |
| <b>Weight (net):</b>                | 950 g (~34 oz)  |
| <b>Gross weight:</b>                | 1150 g (~37 oz)   |
| <b>Risk group (DIN EN 62471):</b>   | free group  |
| <b>Markings:</b>                    | CE, UKCA, ETL Listed (5003529), Ecolab, HACCP                 |
| <b>Mounting accessories:</b>        | included light holder made of metal-detectable PP             |
| <b>Made in:</b>                     | Germany   |
| <b>Feature:</b>                     | RGB-W: Illumination and beacon in one light                   |