



LED-Industrieleuchte mit Signalfunktion



Product-Nr.	110190-01
EAN:	4260556624600
Model:	INROLED_50 Ecolab RGB-W
Order number:	110190-01
Model:	INROLED_50 Ecolab RGB-W
Type:	LED tube light
Illuminant:	SMD RGB-W Cluster LED
Power consumption white:	~19 W
White lamp luminous flux:	~19 W
Lamp luminous efficiency:	126 lm/W
Light colour white:	daylight white (5200 - 5700K)
Power consumption RED:	~18 W
Lamp luminous flux RED:	480 lm
Power consumption GREEN:	~5 W
Lamp luminous flux GREEN:	710 lm
Power consumption BLUE:	~18 W
Lamp luminous flux BLUE:	300 lm
Light distribution:	direct
Connected load:	24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W)
Connection (connector):	M12 A-type encoded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-30... +55 °C (several colours +35 °C) (-22... 131 °F; 95 °F)
Colour rendering WHITE (Ra):	>85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	polycarbonate, soft, shatterproof with Ecolab coating
impact resistance:	IK09
Height [B] x Width [C]:	Ø50 mm (Ø 1,97")
Length [A]:	565 mm (22,24")
Weight (net):	950 g (~34 oz)
Gross weight:	1150 g (~37 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529), Ecolab, HACCP
Mounting accessories:	included light holder made of metal-detectable PP
Made in:	Germany
Feature:	RGB-W: Illumination and beacon in one light