


LED surface-mounted luminaire for machines



Product-Nr.	110510-02
EAN:	4260556621357
Model:	TUBELED_70 DC



110510-02



Order number:	110510-02
Model:	TUBELED_70 DC
Type:	LED surface-mounted luminaire for machines
Illuminant:	High Power LED
Power consumption:	~49 W
Lamp luminous flux:	7596 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC ± 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-30 °C - +70 °C (-22 °F - 158 °F)
Colour rendering (Ra):	>85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	tempered glass, frosted, shatterproof
Height [B] x Width [C]:	Ø 70 mm (~2,76“)
Length [A]:	1100 mm (~43,31“)
Weight (net):	2950 g (~104 oz)
Gross weight:	3750 g (~132 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	optional via accessories
Mounting accessories:	optional
Made in:	Germany
Feature:	retrofitting: standardised LED luminaire for 1:1 replacement

Irrtümer, Systemfehler und Änderungen vorbehalten./
Errors and technical changes excepted. 6.2.2025

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com