




LED-Maschinenleuchte



Product-Nr.	110714-02
EAN:	4260556621388
Model:	TUBELED_70 DC
Order number:	110714-02
Model:	TUBELED_70 DC
Type:	LED surface-mounted luminaire for machines
Illuminant:	High Power LED
Power consumption:	~79 W
Lamp luminous flux:	9156 lm
Lamp luminous efficiency:	ca. 116 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	60°
Operating temperature:	-30... +70 °C (-22... 158 °F)
Colour rendering (Ra):	> 80
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	safety glass, frosted, shatterproof
Height [B] x Width [C]:	\varnothing 70 mm (\varnothing 2,76")
Length [A]:	1580 mm (62,2")
Weight (net):	4200 g (~148 oz)
Gross weight:	5450 g (~192 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003526)
Dimmable:	via optional accessory
Mounting accessories:	optional
Made in:	Germany
Feature:	retrofitting: standardised LED luminaire for 1:1 replacement