



LED-Systemleuchte



Product-Nr.	110914-12
EAN:	4260556620329
Model:	UNILED SL DC
Order number:	110914-12
Model:	UNILED SL DC
Type:	LED system light and workplace lighting
Illuminant:	SMD LED
Power consumption:	~24 W
Lamp luminous flux:	3798 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP50
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-10... +60 °C (14... 140 °F)
Colour rendering (Ra):	>85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	plastic soft
Height [B] x Width [C]:	35 mm x 85 mm (1,38" x 3,35")
Length [A]:	545 mm / 575 mm (21,46" / 22,64")
Weight (net):	850 g (~30 oz)
Gross weight:	1300 g (~46 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	via optional accessory
Mounting accessories:	optional
Made in:	Germany
Feature:	homogeneous lighting, shadow- and glare-free