



LED system light and workplace lighting

Product-Nr.	110914-83
EAN:	4260556623580
Model:	UNILED SL AC Zugpendel
Order number:	110914-83
Model:	UNILED SL AC Zugpendel
Type:	LED system light and workplace lighting
Illuminant:	SMD LED
Power consumption:	~34 W
Lamp luminous flux:	5120 lm
Lamp luminous efficiency:	127 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	220-240V AC \pm 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	1 pair of adjustable pull pendants, ceiling transfer point via two open cable ends
Degree of protection:	IP50
Class of protection:	I
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	-10 °C -> +60 °C (14 °F -> 140 °F)
Colour rendering (Ra):	>80
Lamps lifetime:	> 50.000 h (L80/B10)
Housing material:	aluminium
Cover material:	micro prisms cover
Height [B] x Width [C]:	35 mm x 85 mm (~1,38" x ~3,35")
Length [A]:	1070 mm (~42,13")
Rise and fall range of adjustable pendants:	~740 mm - 1900 mm
Weight (net):	1900 g (~67 oz)
Gross weight:	2750 g (~97 oz)
Risk group (DIN EN 62471):	group 1
Markings:	CE, UKCA
Made in:	Germany
Feature:	light intensity variable via adjustable pull pendants

