



E<sub>rotel</sub>= 479 lux E<sub>rox</sub>= 649 lux

277 lux

## LED-Systemleuchte mit Zugpendel

**Product-Nr.** 110914-85

Model: UNILED SL AC Zugpendel

4260556624822

Order number: 110914-85

EAN:

Model: UNILED SL AC Zugpendel

Type: LED ceiling worklight Illuminant: SMD LED

Power consumption: ~17 W

Lamp luminous flux: 2060 Im

Lamp luminous efficiency: 127 Im/W

Light distribution: direkt

Light colour: Daylight white (5,200 - 5,700K)Connected load: 220-240V AC  $\pm$  10%, 50-60 Hz

Power supply: integrated

Connection (connector): 1 pair of rise and fall attachment, 1x 230V ceiling transfer point, 2 open cable

ends

Degree of protection: IP50
Class of protection: I

Glare control: Prismatic cover

Beam angle (optics): 100°

Operating temperature: -10... +60 °C

Colour rendering (Ra): > 80

Lamps lifetime: > 50.000 h (L80/B10)

Housing material: Aluminium

Cover material: Microprismatic plastic

Height [B] x Width [C]: 35 mm x 85 mm

Length [A]: 570 mm

Rise and fall range of adjustable ~340 mm - 1300 mm pendants:

Weight (net): 1150 g

Gross weight: 1600 g
Risk group (DIN EN 62471): Group 1
Markings: CE

Made in: Germany

Feature: Light intensity can be adjusted manually using a rise and fall attachment

