


LED-Signalleuchte



Product-Nr.	110994-12
EAN:	4260556623450
Model:	UNILED SL RGB-W
Order number:	110994-12
Model:	UNILED SL RGB-W
Type:	LED system and workplace light
Illuminant:	RGB SMD + SMD LED
Power consumption white:	~19 W
White lamp luminous flux:	~19 W
Lamp luminous efficiency:	126 lm/W
Light colour white:	daylight white (5200 - 5700K)
Power consumption RED:	~18 W
Lamp luminous flux RED:	480 lm
Power consumption GREEN:	~5 W
Lamp luminous flux GREEN:	710 lm
Power consumption BLUE:	~18 W
Lamp luminous flux BLUE:	300 lm
Light distribution:	direct
Connected load:	24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W)
Connection (connector):	M12 A-type encoded
Degree of protection:	IP50
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-10... +50 °C (14... 122 °F)
Colour rendering WHITE (Ra):	>80
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	plastics, soft
Height [B] x Width [C]:	35 mm x 85 mm (1,38 x 3,35")
Length [A]:	545 mm (21,46")
Weight (net):	850 g (~30 oz)
Gross weight:	1300 g (~46 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529)
Mounting accessories:	optional
Made in:	Germany
Feature:	RGB-W: Illumination and beacon in one light