


## LED-Signalleuchte



|                                     |  |
|-------------------------------------|--|
| <b>Product-Nr.</b>                  | 110994-13                                    |
| <b>EAN:</b>                         | 4260556623467                                |
| <b>Model:</b>                       | UNILED SL RGB-W                              |
| Order number:                       | 110994-13                                    |
| <b>Model:</b>                       | UNILED SL RGB-W                              |
| <b>Type:</b>                        | LED system and workplace light               |
| <b>Illuminant:</b>                  | RGB SMD + SMD LED                            |
| <b>Power consumption white:</b>     | ~38 W  |
| <b>White lamp luminous flux:</b>    | ~38 W  |
| <b>Lamp luminous efficiency:</b>    | 126 lm/W                                     |
| <b>Light colour white:</b>          | daylight white (5200 - 5700K)                |
| <b>Power consumption RED:</b>       | ~36 W  |
| <b>Lamp luminous flux RED:</b>      | 960 lm                                       |
| <b>Power consumption GREEN:</b>     | ~10 W  |
| <b>Lamp luminous flux GREEN:</b>    | 1420 lm                                      |
| <b>Power consumption BLUE:</b>      | ~36 W  |
| <b>Lamp luminous flux BLUE:</b>     | 600 lm                                       |
| <b>Light distribution:</b>          | direct                                       |
| <b>Connected load:</b>              | 24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W) |
| <b>Connection (connector):</b>      | M12 A-type encoded                           |
| <b>Degree of protection:</b>        | IP50   |
| <b>Class of protection:</b>         | III  |
| <b>Glare control:</b>               | opal white                                   |
| <b>Beam angle (optics):</b>         | 100°   |
| <b>Operating temperature:</b>       | -10... +50 °C (14... 122 °F)                 |
| <b>Colour rendering WHITE (Ra):</b> | > 80   |
| <b>Lamps lifetime:</b>              | > 60.000 h (L80/B10)                         |
| <b>Housing material:</b>            | aluminium                                    |
| <b>Cover material:</b>              | plastics, soft                               |
| <b>Height [B] x Width [C]:</b>      | 35 mm x 85 mm (1,38 x 3,35")                 |
| <b>Length [A]:</b>                  | 1045 mm (41,14")                             |
| <b>Weight (net):</b>                | 1600 g (~56 oz)                              |
| <b>Gross weight:</b>                | 2450 g (~86 oz)                              |
| <b>Risk group (DIN EN 62471):</b>   | free group                                   |
| <b>Markings:</b>                    | CE, UKCA, ETL Listed (5003529)               |
| <b>Mounting accessories:</b>        | optional                                     |
| <b>Made in:</b>                     | Germany                                      |
| <b>Feature:</b>                     | RGB-W: Illumination and beacon in one light  |