



LED surface-mounted luminaire



Product-Nr. 111010-07

EAN: 4260556624068

Model: LEANLED II Clear

Order number: 111010-07

Model: LEANLED II Clear

Type: LED surface-mounted luminaire

Illuminant: SMD LED

Power consumption: ~37 W

Lamp luminous flux: 6012 lm

Lamp luminous efficiency: 155 lm/W

Light distribution: direct

Light colour: 5600K 3-step MacAdam

Connected load: 24V DC $\pm$ 10%

Connection (connector): M12 A-coded

Degree of protection: IP54

Class of protection: III

Beam angle (optics): 120°

Operating temperature: 14 °F - 140 °F

Colour rendering (Ra): >85

Lamps lifetime: > 100,000 h (L80/B10)

Housing material: aluminium

Cover material: Polycarbonat, clear, shatterproof

Height [B] x Width [C]: ~1,22" x ~1,02"

Length [A]: ~59,84"

Weight (net): ~34 oz

Gross weight: ~51 oz

Risk group (DIN EN 62471): free group

Markings: CE, UKCA, ETL Listed (5003529), D mark

Dimmable: optional via accessories

Mounting accessories: 2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope

Made in: Germany

