

LED-Maschinenleuchte



| | |
|--------------------|---------------------|
| Product-Nr. | 111010-11 |
| EAN: | 4260556624075 |
| Model: | LEANLED II opalweiß |

| | |
|----------------------------|---|
| Order number: | 111010-11 |
| Model: | LEANLED II opalweiß |
| Type: | LED surface-mounted luminaire |
| Illuminant: | SMD LED |
| Power consumption: | ~4 W |
| Lamp luminous flux: | 668 lm |
| Lamp luminous efficiency: | 155 lm/W |
| Light distribution: | direct |
| Light colour: | daylight white (5200 - 5700K) |
| Connected load: | 24V DC ± 10% |
| Connection (connector): | M12 A-type encoded |
| Degree of protection: | IP54 |
| Class of protection: | III |
| Glare control: | opal white |
| Beam angle (optics): | 120° |
| Operating temperature: | -10... +60 °C (14... 140 °F) |
| Colour rendering (Ra): | > 85 |
| Lamps lifetime: | > 60.000 h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | Polycarbonate, soft |
| Height [B] x Width [C]: | 31 mm x 26 mm (1,22" x 1,02") |
| Length [A]: | 180 mm (7,09") |
| Weight (net): | 180 g (~6 oz) |
| Gross weight: | 330 g (~12 oz) |
| Risk group (DIN EN 62471): | free group |
| Markings: | CE, UKCA, ETL Listed (5003526) |
| Dimmable: | via optional accessory |
| Mounting accessories: | 2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope |
| Made in: | Germany |

