

LED-Maschinenleuchte



Product-Nr.	111010-14
EAN:	4260556624105
Model:	LEANLED II opalweiß

Order number:	111010-14
Model:	LEANLED II opalweiß
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED

Power consumption:	~13 W
Lamp luminous flux:	2004 lm
Lamp luminous efficiency:	155 lm/W

Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)

Connected load:	24V DC ± 10%
Connection (connector):	M12 A-type encoded

Degree of protection:	IP54
Class of protection:	III

Glare control:	opal white
Beam angle (optics):	120°

Operating temperature:	-10... +60 °C (14... 140 °F)
Colour rendering (Ra):	> 85

Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium

Cover material:	polycarbonate, soft
Height [B] x Width [C]:	31 mm x 26 mm (1,22" x 1,02")

Length [A]:	520 mm (20,47")
Weight (net):	350 g (~12 oz)

Gross weight:	600 g (~21 oz)
Risk group (DIN EN 62471):	free group

Markings:	CE, UKCA, ETL Listed (5003526)
Dimmable:	via optional accessory

Mounting accessories:	2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope
Made in:	Germany

