

LED-Maschinenleuchte



Product-Nr.	111010-21
EAN:	4260556624143
Model:	LEANLED II klar kaskadierbar

Order number:	111010-21
Model:	LEANLED II klar kaskadierbar
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED

Power consumption:	~4 W
Lamp luminous flux:	668 lm
Lamp luminous efficiency:	155 lm/W

Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)

Connected load:	24V DC ± 10%
Connection (connector):	M12 A-type encoded

Degree of protection:	IP54
Class of protection:	III

Beam angle (optics):	120°
Operating temperature:	-10... +60 °C (14... 140 °F)

Colour rendering (Ra):	>85
Lamps lifetime:	> 60.000 h (L80/B10)

Housing material:	aluminium
Cover material:	polycarbonat, clear, shatterproof

Height [B] x Width [C]:	31 mm x 26 mm (1,22" x 1,02")
Length [A]:	180 mm (7,09")

Weight (net):	180 g (~6 oz)
Gross weight:	330 g (~12 oz)

Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003526)

Dimmable:	via optional accessory
Mounting accessories:	2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope

Made in:	Germany
-----------------	---------

Feature: cascadable, several luminaires can be interlinked electrically. The entire power consumption may not exceed 4A DC.

