




## LED surface-mounted luminaire



|                            |                                                                                                                  |
|----------------------------|------------------------------------------------------------------------------------------------------------------|
| Product-Nr.                | 111010-21                                                                                                        |
| EAN:                       | 4260556624143                                                                                                    |
| Model:                     | LEANLED II Clear Cascadeable                                                                                     |
| Order number:              | 111010-21                                                                                                        |
| Model:                     | LEANLED II Clear Cascadeable                                                                                     |
| Type:                      | LED surface-mounted luminaire                                                                                    |
| Illuminant:                | SMD LED                                                                                                          |
| Power consumption:         | ~4 W                                                                                                             |
| Lamp luminous flux:        | 668 lm                                                                                                           |
| Lamp luminous efficiency:  | 155 lm/W                                                                                                         |
| Light distribution:        | direct                                                                                                           |
| Light colour:              | 5600K 3-step MacAdam                                                                                             |
| Connected load:            | 24V DC $\pm$ 10%                                                                                                 |
| Connection (connector):    | M12 A-coded                                                                                                      |
| Degree of protection:      | IP54                                                                                                             |
| Class of protection:       | III                                                                                                              |
| Beam angle (optics):       | 120°                                                                                                             |
| Operating temperature:     | 14 °F - 140 °F                                                                                                   |
| Colour rendering (Ra):     | >85                                                                                                              |
| Lamps lifetime:            | > 100,000 h (L80/B10)                                                                                            |
| Housing material:          | aluminium                                                                                                        |
| Cover material:            | polycarbonat, clear, shatterproof                                                                                |
| Height [B] x Width [C]:    | ~1,22" x ~1,02"                                                                                                  |
| Length [A]:                | ~7,09"                                                                                                           |
| Weight (net):              | ~7 oz                                                                                                            |
| Gross weight:              | ~9 oz                                                                                                            |
| Risk group (DIN EN 62471): | free group                                                                                                       |
| Markings:                  | CE, UKCA, ETL Listed (5003529), D mark                                                                           |
| Dimmable:                  | optional via accessories                                                                                         |
| Mounting accessories:      | 2 pairs mounting holders (holder for swivel or planar moun-ting) in delivery scope                               |
| Made in:                   | Germany                                                                                                          |
| Feature:                   | cascable, several luminaires can be interlinked electrically. The entire power consumption may not exceed 4A DC. |
| cascable:                  | yes                                                                                                              |