

LED-Maschinenleuchte



Product-Nr.	111010-23
EAN:	4260556624167
Model:	LEANLED II klar kaskadierbar

Order number:	111010-23
Model:	LEANLED II klar kaskadierbar
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Power consumption:	~8 W
Lamp luminous flux:	1336 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC ± 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP54
Class of protection:	III
Beam angle (optics):	120°
Operating temperature:	-10... +60 °C (14... 140 °F)
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	Polycarbonat, clear, shatterproof
Height [B] x Width [C]:	31 mm x 26 mm (1,22" x 1,02")
Length [A]:	350 mm (13,78")
Weight (net):	300 g (~11 oz)
Gross weight:	450 g (~16 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003526)
Dimmable:	via optional accessory
Mounting accessories:	2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope
Made in:	Germany
Feature:	cascadable, several luminaires can be interlinked electrically. The entire power consumption may not exceed 4A DC.

