




LED surface-mounted luminaire



Product-Nr.	111010-25
EAN:	4260556624181
Model:	LEANLED II Clear Cascadeable
Order number:	111010-25
Model:	LEANLED II Clear Cascadeable
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Power consumption:	~19 W
Lamp luminous flux:	3004 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	direct
Light colour:	5600K 3-step MacAdam
Connected load:	24V DC $\pm$ 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP54
Class of protection:	III
Beam angle (optics):	120°
Operating temperature:	14 °F - 140 °F
Colour rendering (Ra):	>85
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	polycarbonat, clear, shatterproof
Height [B] x Width [C]:	~1,22" x ~1,02"
Length [A]:	~29,92"
Weight (net):	~22 oz
Gross weight:	~25 oz
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529), D mark
Dimmable:	optional via accessories
Mounting accessories:	2 pairs mounting holders (holder for swivel or planar moun-ting) in delivery scope
Made in:	Germany
Feature:	cascable, several luminaires can be interlinked electrically. The entire power consumption may not exceed 4A DC.
cascable:	yes