

LED-Maschinenleuchte



Product-Nr.	111010-26
EAN:	4260556624198
Model:	LEANLED II klar kaskadierbar

Order number:	111010-26
Model:	LEANLED II klar kaskadierbar
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED

Power consumption:	~24 W
Lamp luminous flux:	4008 lm
Lamp luminous efficiency:	155 lm/W

Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)

Connected load:	24V DC ± 10%
Connection (connector):	M12 A-type encoded

Degree of protection:	IP54
Class of protection:	III

Beam angle (optics):	120°
Operating temperature:	-10... +60 °C (14... 140 °F)
Colour rendering (Ra):	> 85

Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium

Cover material:	Polycarbonat, clear, shatterproof
Height [B] x Width [C]:	31 mm x 26 mm (1,22" x 1,02")

Length [A]:	1020 mm (40,16")
Weight (net):	700 g (~25 oz)

Gross weight:	1000 g (~35 oz)
Risk group (DIN EN 62471):	free group

Markings:	CE, UKCA, ETL Listed (5003526)
Dimmable:	via optional accessory

Mounting accessories:	2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope
Made in:	Germany

Feature: cascadable, several luminaires can be interlinked electrically. The entire power consumption may not exceed 4A DC.

