

**LED-Maschinenleuchte**



**Product-Nr.** 111010-27

**EAN:** 4260556624204

**Model:** LEANLED II klar kaskadierbar

**Order number:** 111010-27

**Model:** LEANLED II klar kaskadierbar

**Type:** LED surface-mounted luminaire

**Illuminant:** SMD LED

**Power consumption:** ~37 W

**Lamp luminous flux:** 6012 lm

**Lamp luminous efficiency:** 155 lm/W

**Light distribution:** direct

**Light colour:** daylight white (5200 - 5700K)

**Connected load:** 24V DC ± 10%

**Connection (connector):** M12 A-type encoded

**Degree of protection:** IP54

**Class of protection:** III

**Beam angle (optics):** 120°

**Operating temperature:** -10... +60 °C (14... 140 °F)

**Colour rendering (Ra):** > 85

**Lamps lifetime:** > 60.000 h (L80/B10)

**Housing material:** aluminium, plastics

**Cover material:** polycarbonat, clear, shatterproof

**Height [B] x Width [C]:** 31 mm x 26 mm (1,22" x 1,02")

**Length [A]:** 1520 mm (59,84")

**Weight (net):** 950 g (~34 oz)

**Gross weight:** 1450 g (~51 oz)

**Risk group (DIN EN 62471):** free group

**Markings:** CE, UKCA, ETL Listed (5003526)

**Dimmable:** via optional accessory

**Mounting accessories:** 2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope

**Made in:** Germany

**Feature:** cascadable, several luminaires can be interlinked electrically. The entire power consumption may not exceed 4A DC.

