

LED surface-mounted luminaire



Product-Nr.	111010-33
EAN:	4260556624235
Model:	LEANLED II Opal White Cascadeable

Order number:	111010-33
Model:	LEANLED II Opal White Cascadeable
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Power consumption:	~8 W
Lamp luminous flux:	1336 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	direct
Light colour:	5600K 3-step MacAdam
Connected load:	24V DC $\pm$ 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP54
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	120°
Operating temperature:	14 °F - 140 °F
Colour rendering (Ra):	>85
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	Polycarbonate, soft
Height [B] x Width [C]:	~1,22" x ~1,02"
Length [A]:	~13,78"
Weight (net):	~10 oz
Gross weight:	~13 oz
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529), D mark
Dimmable:	optional via accessories
Mounting accessories:	2 pairs mounting holders (holder for swivel or planar moun-ting) in delivery scope
Made in:	Germany
Feature:	cascadable, several luminaires can be interlinked electrically.
cascadable:	yes

