


LED surface-mounted luminaire for machines



Product-Nr.	111010-41
EAN:	4260556627816
Model:	LEANLED II Basic-Line Clear
Order number:	111010-41
Model:	LEANLED II Basic-Line Clear
Type:	LED surface-mounted luminaire for machines
Illuminant:	1 x 2941-5051-00-LE-BL166
Power consumption:	~4 W
Lamp luminous flux:	589 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	direct
Light colour:	5600K 3-step MacAdam
Number of poles:	3
Assignment of PIN 1 input / output:	VCC
Assignment of PIN 2 input / output:	N.C.
Assignment of PIN 3 input / output:	GND
Assignment of PIN 4 input / output:	VCC
Assignment of PIN 5 input / output:	N.C.
Connected load:	24V DC $\pm$ 10%
Maximum power consumption White:	158 mA
Power supply:	external
Connection (connector):	M12 A-coded
Class of protection:	III
Glare control:	clear
Beam angle (optics):	120°
Colour rendering (Ra):	>80
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	Polycarbonat
Height [B] x Width [C]:	31 mm x 26 mm (~1,22" x ~1,02")
Length [A]:	180 mm (~7,09")
Mounting:	M4 rear channels, swivel and fixed angle
Weight (net):	210 g (~7 oz)
Gross weight:	250 g (~9 oz)
Risk group (DIN EN 62471):	free group
Mounting accessories:	Including swivel and fixed bracket
Made in:	Germany
cascadable:	no