


LED surface-mounted luminaire for machines



Product-Nr.	111010-42
EAN:	4260556627823
Model:	LEANLED II Basic-Line Clear
Order number:	111010-42
Model:	LEANLED II Basic-Line Clear
Type:	LED surface-mounted luminaire for machines
Illuminant:	1 x 2941-5052-00-LE-BL249
Power consumption:	~6 W
Lamp luminous flux:	881 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	direct
Light colour:	5600K 3-step MacAdam
Number of poles:	3
Assignment of PIN 1 input / output:	VCC
Assignment of PIN 2 input / output:	N.C.
Assignment of PIN 3 input / output:	GND
Assignment of PIN 4 input / output:	VCC
Assignment of PIN 5 input / output:	N.C.
Connected load:	24V DC $\pm$ 10%
Maximum power consumption White:	238 mA
Power supply:	external
Connection (connector):	M12 A-coded
Class of protection:	III
Glare control:	clear
Beam angle (optics):	120°
Colour rendering (Ra):	>80
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	Polycarbonat
Height [B] x Width [C]:	31 mm x 26 mm (~1,22" x ~1,02")
Length [A]:	260 mm (~10,24")
Mounting:	M4 rear channels, swivel and fixed angle
Weight (net):	240 g (~8 oz)
Gross weight:	280 g (~10 oz)
Risk group (DIN EN 62471):	free group
Mounting accessories:	Including swivel and fixed bracket
Made in:	Germany
cascadable:	no