


LED surface-mounted luminaire for machines



|                                            |                                            |
|--------------------------------------------|--------------------------------------------|
| <b>Product-Nr.</b>                         | 111010-51                                  |
| <b>EAN:</b>                                | 4260556627885                              |
| <b>Model:</b>                              | LEANLED II Basic-Line Opal White           |
| Order number:                              | 111010-51                                  |
| <b>Model:</b>                              | LEANLED II Basic-Line Opal White           |
| <b>Type:</b>                               | LED surface-mounted luminaire for machines |
| <b>Illuminant:</b>                         | 1 x 2941-5051-00-LE-BL166                  |
| <b>Power consumption:</b>                  | ~4 W                                       |
| <b>Lamp luminous flux:</b>                 | 589 lm                                     |
| <b>Lamp luminous efficiency:</b>           | 155 lm/W                                   |
| <b>Light distribution:</b>                 | direct                                     |
| <b>Light colour:</b>                       | 5600K 3-step MacAdam                       |
| <b>Number of poles:</b>                    | 3                                          |
| <b>Assignment of PIN 1 input / output:</b> | VCC                                        |
| <b>Assignment of PIN 2 input / output:</b> | N.C.                                       |
| <b>Assignment of PIN 3 input / output:</b> | GND                                        |
| <b>Assignment of PIN 4 input / output:</b> | VCC                                        |
| <b>Assignment of PIN 5 input / output:</b> | N.C.                                       |
| <b>Connected load:</b>                     | 24V DC $\pm$ 10%                           |
| <b>Maximum power consumption White:</b>    | 158 mA                                     |
| <b>Power supply:</b>                       | external                                   |
| <b>Connection (connector):</b>             | M12 A-coded                                |
| <b>Class of protection:</b>                | III                                        |
| <b>Glare control:</b>                      | opal white                                 |
| <b>Beam angle (optics):</b>                | 120°                                       |
| <b>Colour rendering (Ra):</b>              | >80                                        |
| <b>Lamps lifetime:</b>                     | > 60.000 h (L80/B10)                       |
| <b>Housing material:</b>                   | aluminium                                  |
| <b>Cover material:</b>                     | Polycarbonat                               |
| <b>Height [B] x Width [C]:</b>             | 31 mm x 26 mm (~1,22" x ~1,02")            |
| <b>Length [A]:</b>                         | 180 mm (~7,09")                            |
| <b>Mounting:</b>                           | M4 rear channels, swivel and fixed angle   |
| <b>Weight (net):</b>                       | 210 g (~7 oz)                              |
| <b>Gross weight:</b>                       | 250 g (~9 oz)                              |
| <b>Risk group (DIN EN 62471):</b>          | free group                                 |
| <b>Mounting accessories:</b>               | Including swivel and fixed bracket         |
| <b>Made in:</b>                            | Germany                                    |
| <b>cascadable:</b>                         | no                                         |