




LED surface-mounted light



Product-Nr.	111090-42
EAN:	4260556626819
Model:	SIGNALLED II RGB-W
Order number:	111090-42
Model:	SIGNALLED II RGB-W
Type:	LED surface-mounted light
Illuminant:	SMD RGB-W Cluster LED
Power consumption white:	~7,2 W
White lamp luminous flux:	1150 lm
Lamp luminous efficiency:	159,72 lm/W
Light colour white:	5600K 3-step MacAdam
Power consumption RED:	~2,16 W
Lamp luminous flux RED:	138 lm
Power consumption GREEN:	~1,44 W
Lamp luminous flux GREEN:	252 lm
Power consumption BLUE:	~2,16 W
Lamp luminous flux BLUE:	84 lm
Light distribution:	direct
Connected load:	24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W)
Connection (connector):	M12 A-coded
Degree of protection:	IP54
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	120°
Operating temperature:	14 °F - 122 °F
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	polycarbonate, soft
Height [B] x Width [C]:	~0,98" x ~1,18"
Length [A]:	~10,24"
Weight (net):	~8 oz
Gross weight:	~10 oz
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529), D mark
Dimmable:	no
Mounting accessories:	2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope
Made in:	Germany