LED-Maschinenleuchte

Product-Nr.	111913-01
EAN:	4260556620954
Model:	TOPLED



Order number:	111913-01
Model:	TOPLED
Type:	LED surface-mounted luminaire
Illuminant:	High Power LED
Power consumption:	~8,4 W
Lamp luminous flux:	982 lm
Lamp luminous efficiency:	116 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC ± 10%
Connection (connector):	M12 A-type encoded mit 150 mm Anschlussleitung
Degree of protection:	IP67
Class of protection:	III
Glare control:	ESG frosted, shatterproof
Beam angle (optics):	40°
Operating temperature:	-10... +60 °C (14… 140 °F)
Colour rendering (Ra):	> 80
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	4 mm safety glass
Height [B] x Width [C]:	Ø 50 mm (Ø 1,97“), 23 mm externally (0,91“)
Weight (net):	100 g (~4 oz)
Gross weight:	300 g (~11 oz)
Risk group (DIN EN 62471):	group 1
Markings:	CE, UKCA
Dimmable:	via optional accessory
Mounting accessories:	Mutter M18x1.5 inkl.
Made in:	Germany
Feature:	very bright

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com