LED2WORK
INTELLIGENCE IN LIGHT

LED-Industrieleuchte

Product-Nr.	115010-01
EAN:	4260556621661
Model:	INROLED_70 mit Borosilikatglas-Schutzrohr



Order number:	115010-01
Model:	INROLED_70 mit Borosilikatglas-Schutzrohr
Type:	LED surface mounted tube luminaire
Illuminant:	SMD LED
Power consumption:	~6,5 W
Lamp luminous flux:	1000 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC ± 10%
Degree of protection:	IP67/IP69K
Class of protection:	III
Beam angle (optics):	125°
Operating temperature:	-10... +45 °C (14… 113 °F)
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium inside
Cover material:	safety glass, shatterproof
Height [B] x Width [C]:	Ø 70 mm (Ø 2,76“)
Length [A]:	354 mm (13,94“)
Weight (net):	1200 g (~42 oz)
Gross weight:	1700 g (~60 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	via optional accessory
Mounting accessories:	optional
Made in:	Germany
Feature:	cascadable (max. 4.0 A)

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com