LED2WORK
INTELLIGENCE IN LIGHT

LED-Industrieleuchte

Product-Nr.	115310-04
EAN:	4260556624716
Model:	INROLED_70 mit PC Schutzrohr



Order number:	115310-04
Model:	INROLED_70 mit PC Schutzrohr
Type:	LED surface mounted tube luminaire
Illuminant:	SMD LED
Total output incl. driver:	~23 W
Power consumption:	~21 W
Lamp luminous flux:	3340 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	90-305V AC ± 10%, 50-60 Hz
Power supply:	inbuilt
Degree of protection:	IP67/IP69K
Class of protection:	I
Beam angle (optics):	125°
Operating temperature:	-10... +40 °C (14… 104 °F)
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium inside
Cover material:	polycarbonate, shatterproof
Height [B] x Width [C]:	Ø 70 mm (Ø 2,76“)
Length [A]:	921 mm (36,26“)
Weight (net):	2200 g (~78 oz)
Gross weight:	3150 g (~111 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Mounting accessories:	optional
Made in:	Germany
Feature:	cascadable

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com