

LED-Maschinenleuchte



Product-Nr.	118010-11
EAN:	4260556622828
Model:	TUBELED_40 II Power, kaskadierbar
Order number:	118010-11
Model:	TUBELED_40 II Power, kaskadierbar
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Power consumption:	~8 W
Lamp luminous flux:	1266 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Light Forming Technology
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	diffuser sheet for scattered light, PMMA
Beam angle (optics):	100°
Operating temperature:	-30... +60 °C (-22... 140 °F)
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	safety glass, 4 mm (0,16")
Height [B] x Width [C]:	29 mm x 40 mm (1,14" x 1,57")
Length [A]:	190 mm (7,48")
Weight (net):	260 g (~9 oz)
Gross weight:	450 g (~16 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003526)
Dimmable:	via optional accessory
Mounting accessories:	optional
Made in:	Germany
Feature:	cascadable

