



LED surface-mounted luminaire



Product-Nr.	118110-07
EAN:	4260556628769
Model:	TUBELED_40 II Basic-Line AC
Order number:	118110-07
Model:	TUBELED_40 II Basic-Line AC
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Total output incl. driver:	~8,5 W
Power consumption:	~8,5 W
Lamp luminous flux:	1030 lm
Lamp luminous efficiency:	127 lm/W
Light distribution:	Direct
Light colour:	5600K 3-step MacAdam
Colour rendering (Ra):	>80
Supply voltage:	230V AC \pm 10%, 50-60 Hz
Connection (connector):	M12 S-coded
Number of poles:	3
Degree of protection:	IP67/IP69K
Class of protection:	I
Glare control:	Diffuser, tempered glass
Beam angle (optics):	100°
Operating temperature:	-30 °C - +50 °C (-22 °F - 122 °F)
Storage temperature:	-30 °C - +80 °C (-22 °F - 176 °F)
Lamps lifetime:	> 50.000 h (L80/B10)
Housing material:	Aluminium
Cover material:	Tempered glass, 4 mm
Height [B] x Width [C]:	29 mm x 40 mm (~1,14" x ~1,57")
Length [A]:	280 mm (~11,02")
Weight (net):	400 g (~14 oz)
Gross weight:	550 g (~19 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, D mark
Dimmable:	No
Mounting accessories:	Optional
Made in:	Germany
Feature:	230 V AC connection, temperature-resistant
Note:	Operation at 50 Hz – not suitable for camera applications or fast-rotating parts.
cascadable:	No