



LED surface-mounted luminaire for machines



Product-Nr.	118110-11
EAN:	4260556622705
Model:	TUBELED_40 II Power, Cascadeable
Order number:	118110-11
Model:	TUBELED_40 II Power, Cascadeable
Type:	LED surface-mounted luminaire for machines
Illuminant:	SMD LED
Power consumption:	~12 W
Lamp luminous flux:	1899 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Light Forming Technology
Light colour:	5600K 3-step MacAdam
Connected load:	24V DC $\pm$ 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	diffused safety glass
Beam angle (optics):	100°
Operating temperature:	-22 °F - 140 °F
Colour rendering (Ra):	>85
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	tempered glass, 4 mm (0,16")
Height [B] x Width [C]:	~1,14" x ~1,57"
Length [A]:	~11,02"
Weight (net):	~14 oz
Gross weight:	~19 oz
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529), D mark
Dimmable:	optional via accessories
Mounting accessories:	optional
Made in:	Germany
Feature:	100% CNC approved