


LED surface-mounted luminaire



| | |
|-----------------------------------|---|
| Product-Nr. | 118310-07 |
| EAN: | 4260556628776 |
| Model: | TUBELED_40 II Basic-Line AC |
| Order number: | 118310-07 |
| Model: | TUBELED_40 II Basic-Line AC |
| Type: | LED surface-mounted luminaire |
| Illuminant: | SMD LED |
| Total output incl. driver: | ~17 W |
| Power consumption: | ~17 W |
| Lamp luminous flux: | 2060 lm |
| Lamp luminous efficiency: | 127 lm/W |
| Light distribution: | Direct |
| Light colour: | 5600K 3-step MacAdam |
| Colour rendering (Ra): | >80 |
| Supply voltage: | 230V AC \pm 10%, 50-60 Hz |
| Connection (connector): | M12 S-coded |
| Number of poles: | 3 |
| Degree of protection: | IP67/IP69K |
| Class of protection: | I |
| Glare control: | Diffuser, tempered glass |
| Beam angle (optics): | 100° |
| Operating temperature: | -30 °C - +50 °C (-22 °F - 122 °F) |
| Storage temperature: | -30 °C - +80 °C (-22 °F - 176 °F) |
| Lamps lifetime: | > 50.000 h (L80/B10) |
| Housing material: | Aluminium |
| Cover material: | Tempered glass, 4 mm |
| Height [B] x Width [C]: | 29 mm x 40 mm (~1,14" x ~1,57") |
| Length [A]: | 540 mm (~21,26") |
| Weight (net): | 650 g (~23 oz) |
| Gross weight: | 900 g (~32 oz) |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, D mark |
| Dimmable: | No |
| Mounting accessories: | Optional |
| Made in: | Germany |
| Feature: | 230 V AC connection, temperature-resistant |
| Note: | Operation at 50 Hz – not suitable for camera applications or fast-rotating parts. |
| cascadable: | No |