



 Darstellbares Farbspektrum /
 Displayable colour spectrum


Mischfarben werden mit der
 Ansteuerung mehrerer Eingänge
 gleichzeitig erreicht. /
 Mixed colours will be achieved
 with the control of multiple
 inputs simultaneously.



Product-Nr.	118390-02
EAN:	4260556623122
Model:	TUBELED_40 II RGB-W ECO
Order number:	118390-02
Model:	TUBELED_40 II RGB-W ECO
Illuminant:	SMD RGB-W Cluster LED
Power consumption white:	~14 W
White lamp luminous flux:	2300 lm
Lamp luminous efficiency:	~165 lm/W
Light colour white:	5000K 3-step MacAdam
Power consumption RED:	~4,3 W
Lamp luminous flux RED:	276 lm
Power consumption GREEN:	~2,9 W
Lamp luminous flux GREEN:	504 lm
Power consumption BLUE:	~4,3 W
Lamp luminous flux BLUE:	168 lm
Light distribution:	light forming technology
Connected load:	24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W)
Connection (connector):	M12 A-coded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	diffused safety glass
Beam angle (optics):	100°
Operating temperature:	-22 °F - 158 °F
Colour rendering WHITE (Ra):	>85
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	tempered glass, shatterproof
Height [B] x Width [C]:	~1,14" x ~1,57"
Length [A]:	~21,26"
Weight (net):	~23 oz
Gross weight:	~32 oz
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529), D mark
Mounting accessories:	optional
Made in:	Germany
Feature:	RGB-W: Illumination and beacon in one light