




LED-Maschinenleuchte



Product-Nr.	118510-02
EAN:	4260556622750
Model:	TUBELED_40 II ECO
Order number:	118510-02
Model:	TUBELED_40 II ECO
Type:	LED surface-mounted luminaire for machines
Illuminant:	SMD LED
Power consumption:	~24 W
Lamp luminous flux:	4008 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Light Forming Technology
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	diffused safety glass
Beam angle (optics):	100°
Operating temperature:	-30... +70 °C (-22... 158 °F)
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	safety glass, 4 mm (0,16")
Height [B] x Width [C]:	29 mm x 40 mm (1,14" x 1,57")
Length [A]:	1040 mm (40,94")
Weight (net):	1300 g (~46 oz)
Gross weight:	1650 g (~58 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003526)
Dimmable:	via optional accessory
Mounting accessories:	optional
Made in:	Germany
Feature:	resistant to high temperatures