



## LED-Signalleuchte

<b>Product-Nr.</b>	118590-01
<b>EAN:</b>	4260556623627
<b>Model:</b>	TUBELED_40 II RGB-W Power

Order number:	118590-01
<b>Model:</b>	TUBELED_40 II RGB-W Power
<b>Type:</b>	LED surface-mounted light
<b>Illuminant:</b>	SMD RGB-W Cluster LED
<b>Power consumption white:</b>	~38 W
<b>White lamp luminous flux:</b>	~38 W
<b>Lamp luminous efficiency:</b>	~126 lm/W
<b>Light colour white:</b>	daylight white (5200 - 5700K)
<b>Power consumption RED:</b>	~36 W
<b>Lamp luminous flux RED:</b>	960 lm
<b>Power consumption GREEN:</b>	~10 W
<b>Lamp luminous flux GREEN:</b>	1380 lm
<b>Power consumption BLUE:</b>	~36 W
<b>Lamp luminous flux BLUE:</b>	600 lm
<b>Light distribution:</b>	light forming technology
<b>Connected load:</b>	24 V DC -10 % +7 % (RGB) – 24 V DC $\pm$ 10 % (W)
<b>Connection (connector):</b>	M12 A-type encoded
<b>Degree of protection:</b>	IP67/IP69K
<b>Class of protection:</b>	III
<b>Glare control:</b>	diffused safety glass
<b>Beam angle (optics):</b>	100°
<b>Operating temperature:</b>	-30... +60 °C (-22... 140 °F)
<b>Colour rendering WHITE (Ra):</b>	>80
<b>Lamps lifetime:</b>	> 60.000 h (L80/B10)
<b>Housing material:</b>	aluminium
<b>Cover material:</b>	safety glass, shatterproof
<b>Height [B] x Width [C]:</b>	29 mm x 40 mm (1,14" x 1,57")
<b>Length [A]:</b>	1040 mm (40,94")
<b>Weight (net):</b>	1300 g (~46 oz)
<b>Gross weight:</b>	1650 g (~58 oz)
<b>Risk group (DIN EN 62471):</b>	free group
<b>Markings:</b>	CE, UKCA, ETL Listed (5003529)
<b>Mounting accessories:</b>	optional
<b>Made in:</b>	Germany
<b>Feature:</b>	RGB-W: Illumination and beacon in one light

Darstellbares Farbspektrum /  
Displayable colour spectrum



Mischfarben werden mit der  
Ansteuerung mehrerer Eingänge  
gleichzeitig erreicht. /  
Mixed colours will be achieved  
with the control of multiple  
inputs simultaneously.

