



LED surface-mounted luminaire for machines



Product-Nr.	118610-06
EAN:	4260556627809
Model:	TUBELED_40 II Basic-Line
Order number:	118610-06
Model:	TUBELED_40 II Basic-Line
Type:	LED surface-mounted luminaire for machines
Illuminant:	SMD LED
Total output incl. driver:	~35 W
Power consumption:	~4 W
Lamp luminous flux:	5355 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	direct
Light colour:	5600K 3-step MacAdam
Number of poles:	3
Assignment of PIN 1 input / output:	VCC
Assignment of PIN 2 input / output:	N.C.
Assignment of PIN 3 input / output:	GND
Assignment of PIN 4 input / output:	VCC
Assignment of PIN 5 input / output:	N.C.
Current load per PIN:	4 A
Connected load:	24V DC $\pm$ 10%
Maximum power consumption White:	1442 mA
Connection (connector):	M12 A-coded
RoHS Directive:	Yes
Protection class (mounting):	IP65, IP67, IP69K
Class of protection:	III
Glare control:	diffused safety glass
Beam angle (optics):	100°
Colour rendering (Ra):	>80
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	tempered glass, 4 mm (0,16")
Height [B] x Width [C]:	29 mm x 40 mm (~1,14" x ~1,57")
Length [A]:	1540 mm (~60,63")
Weight (net):	2020 g (~71 oz)
Gross weight:	2370 g (~84 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Dimmable:	optional über Zubehör
Mounting accessories:	optional
Made in:	Germany