



LED-Maschinenleuchte

Product-Nr.	119310-12
EAN:	4260556624358
Model:	TUBELED_40 Element DC, kaskadierbar
Order number:	119310-12
Model:	TUBELED_40 Element DC, kaskadierbar
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Power consumption:	~13 W
Lamp luminous flux:	2004 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP54
Class of protection:	III
Glare control:	diffuser sheet for scattered light, PMMA
Beam angle (optics):	100°
Operating temperature:	-30... +70 °C (-22... 158 °F)
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium, endcaps made of plastics
Cover material:	PMMA, frosted
Height [B] x Width [C]:	29 mm x 40 mm (1,14" x 1,57")
Length [A]:	540 mm (21,26")
Weight (net):	690 g (~25 oz)
Gross weight:	900 g (~32 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Dimmable:	via optional accessory
Mounting accessories:	optional
Made in:	Germany
Feature:	cascadable, resistant to high temperatures
Note:	Electrical through wiring up to max. 8 A DC at ta max. +30 °C (7 A DC at ta max. +40 °C)