


LED-Maschinenleuchte



| | |
|-----------------------------------|------------------------------------------------------------------------------------------|
| Product-Nr. | 119410-12 |
| EAN: | 4260556624372 |
| Model: | TUBELED_40 Element DC, kaskadierbar |
| Order number: | 119410-12 |
| Model: | TUBELED_40 Element DC, kaskadierbar |
| Type: | LED surface-mounted luminaire |
| Illuminant: | SMD LED |
| Power consumption: | ~17 W |
| Lamp luminous flux: | 2672 lm |
| Lamp luminous efficiency: | ~155 lm/W |
| Light distribution: | direct |
| Light colour: | daylight white (5200 - 5700K) |
| Connected load: | 24V DC \pm 10% |
| Connection (connector): | M12 A-type encoded |
| Degree of protection: | IP54 |
| Class of protection: | III |
| Glare control: | diffuser sheet for scattered light, PMMA |
| Beam angle (optics): | 100° |
| Operating temperature: | -30... +70 °C (-22... 158 °F) |
| Colour rendering (Ra): | > 85 |
| Lamps lifetime: | > 60.000 h (L80/B10) |
| Housing material: | aluminium, endcaps made of plastics |
| Cover material: | PMMA, frosted |
| Height [B] x Width [C]: | 29 mm x 40 mm (1,14" x 1,57") |
| Length [A]: | 715 mm (28,15") |
| Weight (net): | 890 g (~32 oz) |
| Gross weight: | 1150 g (~41 oz) |
| Risk group (DIN EN 62471): | free group |
| Markings: | CE, UKCA |
| Dimmable: | via optional accessory |
| Mounting accessories: | optional |
| Made in: | Germany |
| Feature: | cascadable, resistant to high temperatures |
| Note: | Electrical through wiring up to max. 8 A DC at ta max. +30 °C (7 A DC at ta max. +40 °C) |