


LED surface-mounted luminaire



Product-Nr.	119610-03
EAN:	4260556624457
Model:	TUBELED_40 Element AC
Order number:	119610-03
Model:	TUBELED_40 Element AC
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Total output incl. driver:	~51 W
Power consumption:	~51 W
Lamp luminous flux:	6180 lm
Lamp luminous efficiency:	127 lm/W
Light distribution:	Light Forming Technology
Light colour:	5000K 3-step MacAdam
Connected load:	220-240V AC \pm 10%, 50-60 Hz
Connection (connector):	M12 S-coded
Degree of protection:	IP54
Class of protection:	I
Glare control:	diffuser sheet for scattered light, PMMA
Beam angle (optics):	100°
Operating temperature:	-30 °C - +50 °C (-22 °F - 122 °F)
Colour rendering (Ra):	>80
Lamps lifetime:	> 50.000 h (L80/B10)
Housing material:	aluminium, endcaps made of plastics
Cover material:	PMMA, frosted
Height [B] x Width [C]:	29 mm x 40 mm (~1,14" x ~1,57")
Length [A]:	1540 mm (~60,63")
Weight (net):	1400 g (~49 oz)
Gross weight:	1800 g (~63 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, D mark
Mounting accessories:	optional
Made in:	Germany
Feature:	220-240V AC Anschluss, temperaturbeständig