



LED adjustable arm light

Product-Nr.	120700-02
EAN:	4260556623184
Model:	UNILED II Gelenkarm TW
Order number:	120700-02
Model:	UNILED II Gelenkarm TW
Type:	LED adjustable arm light
Illuminant:	SUNlike LED
Power consumption:	~25 W
Lamp luminous flux:	2418 lm (6500 K) / 2244 lm (3000 K)
Lamp luminous efficiency:	~98 lm/W (6500K) / ~91 lm/W (3000K)
Light distribution:	direct
Light colour:	warm white (3,000 K) up to daylight white (6,500 K)
Connected load:	24V DC ± 10%
Power supply:	included external PSU 100-240V AC
Connection (connector):	M12 A-coded
Connected load PSU:	110-240V AC
Connection PSU:	EURO plug to M12 connector
Degree of protection:	IP40
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-10 °C -> +40 °C (14 °F -> 104 °F)
Colour rendering (Ra):	>90/98
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium / plastics
Cover material:	plastic soft
Head width [A]:	548 mm (~21,57")
Length articulated arms:	2x 400 mm
Weight (net):	2250 g (~79 oz)
Gross weight:	3950 g (~139 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Dimmable:	internal dimmer with memory function
Mounting accessories:	included table clamp
Made in:	Germany
Feature:	TUNABLE WHITE: very high colour rendering, continuously adjustable light colour from 3000 K up to 6500 K

