



LED adjustable arm light

| | |
|--------------------|---------------------------|
| Product-Nr. | 120710-02 |
| EAN: | 4260556620282 |
| Model: | UNILED II Articulated Arm |

| | |
|----------------------------|--------------------------------------|
| Order number: | 120710-02 |
| Model: | UNILED II Articulated Arm |
| Type: | LED adjustable arm light |
| Illuminant: | SMD LED |
| Power consumption: | ~18,5 W |
| Lamp luminous flux: | 3404 lm |
| Lamp luminous efficiency: | ~184 lm/W |
| Light distribution: | Direct |
| Light colour: | 5700K 3-step MacAdam |
| Colour rendering (Ra): | >90 |
| Supply voltage: | 24V DC ± 10% |
| Power supply: | Included external PSU 100-240V AC |
| Connection (connector): | M12 A-coded |
| Connected load PSU: | 100-240V AC |
| Connection PSU: | EURO plug to M12 connector |
| Degree of protection: | IP40 |
| Class of protection: | III |
| Glare control: | opal white |
| Beam angle (optics): | 100° |
| Operating temperature: | -10 °C - +60 °C (14 °F - 140 °F) |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Housing material: | aluminium / plastics |
| Cover material: | plastic soft |
| Head width [A]: | 548 mm (~21,57") |
| Length articulated arms: | 2x 400 mm (~15,75") |
| Weight (net): | 3650 g (~129 oz) |
| Gross weight: | 4300 g (~152 oz) |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA |
| Dimmable: | Internal dimmer with memory function |
| Mounting accessories: | Included table clamp |
| Made in: | Germany |
| Feature: | dimmable, large radius |

